

DH-HAC-HDW1231G-A

2MP Starlight HDCVI IR Eyeball Camera



- Max 30 fps@1080P
- Starlight, 130dB true WDR, 3D NR
- 3.6mm fixed lens (2.8mm optional)
- CVI/CVBS/AHD/TVI switchable
- Super Adapt
- Built-in mic
- Max. IR length 20m, Smart IR
- IP67, DC 12 V



System Overview

Lite Series is suitable for users who requires high quality monitoring products at a reasonable price. It is cost effective and offers high performance, which makes it an ideal choice for residential and small-medium business applications. This series offers an option of a wide range of technologies such as Full-color and Starlight, providing various solutions for different scenarios.

Functions

Starlight

With the adoption of large sized high performance sensor and large aperture lens, the camera is able to provide incomparable performance even under extreme lowlight environment. The starlight feature allows more details to be captured and accurate color to be recognized at night or in scenes with limited illumination.

Broadcast-quality Audio

Audio information is used as supplementary evidence in video surveillance applications. The HDCVI camera supports audio signal transmission over coaxial cable. In addition, it adopts unique audio processing and transmission technology that best restores source audio and eliminates noise, guaranteeing the quality and effectiveness of collected audio information.

Wide Dynamic Range

With advanced Wide Dynamic Range (WDR) technology, Dahua HDCVI camera provides clear details in the environment of strong brightness contrast. The bright and dark area can get clear video even in high brightness environment or with backlight shadow.

Super Adapt

Embedded with intelligent algorithm, for changing external environment, camera can automatically adjust parameters to present the optimal image, and it solves the trouble of configuration.

Advanced 3DNR

3DNR is noise reduction technology that detects and eliminates random noises by comparing two sequential frames. Dahua's advanced 3DNR technology allows remarkable noise reduction with little impact to sharpness, especially under limited lighting condition. Besides, the advanced 3DNR effectively decreases the band width and saves the storage space.

Smart Illumination

The camera is designed with IR illumination for best lowlight performance. Smart IR is a technology to ensure brightness uniformity in B/W image under low illumination. Dahua's unique Smart IR adjusts to the intensity of camera's infrared LEDs to compensate for the distance of an object, and prevents IR LEDs from overexposing images as the object come closer to the camera.

Protection (IP67, wide voltage)

IP67: The camera passes a series of strict test on dust and soak. It has dust-proof function, and the enclosure can works normal after soaking in 1 m deep water for 30 minutes.

Wide voltage: The camera allows $\pm 30\%$ (for some power supplies) input voltage tolerance (wide voltage range), and it is widely applied to outdoor environment with instable voltage.

Technical Specification					
Camera					
Image Sensor		1/2.8" CMOS			
Max. Resolution		1920 (H) × 1080 (V)			
Pixel		2MP			
Scanning System		Progressive			
Electronic Shutter Speed		PAL: 1/25 s~1/100,000 s NTSC: 1/30 s~1/100,000 s			
S/N Ratio		> 65 dB			
Min. Illumination		0.002 Lux/F1.6, 30 IRE, 0 Lux IR on			
Illumination Distance		20 m (65.6 ft)			
Illuminator On/Off Control		Auto; manual			
Illuminator Number		1 (IR light)			
Pan/Tilt/Rotation Range		Pan: 0°~360° Tilt: 0°~78° Rotation: 0°~360°			
Lens					
Lens Type		Fixed lens			
Mount Type		M12			
Focal Length		2.8 mm; 3.6 mm			
Max. Aperture		F1.6			
Field of View		2.8 mm: H: 102°; V: 54°; D: 120° 3.6 mm: H: 86°; V: 46°; D: 101°			
Iris Type		Fixed iris			
Close Focus Distance		2.8 mm: 0.5 m (1.6 ft) 3.6 mm: 1.1 m (3.6 ft)			
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8 mm	38.6 m (126.6 ft)	15.4 m (50.5 ft)	7.7 m (25.3 ft)	3.9 m (12.8 ft)
	3.6 mm	53.7 m (176.2 ft)	21.5 m (70.5 ft)	10.7 m (35.1 ft)	5.4 m (17.7 ft)
	*DORI (Detect, Observe, Recognize, Identify) is a standard system (EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances. For intelligent function distances, refer to installation and commissioning manual/ project design tool.				
Video					
Frame Rate		CVI: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; AHD: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; TVI: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; CVBS: PAL: 960 × 576H; NTSC: 960 × 480H			
Resolution		1080p (1920 × 1080); 960H (960 × 576/960 × 480)			

Day/Night		Auto switch by ICR
BLC		BLC/WDR/HLC
WDR		130 dB
White Balance		Auto; Area WB
Gain Control		Auto; manual
Noise Reduction		3D NR
Smart IR		Yes
Mirror		Off/On
Privacy Masking		Off/On (8 area, rectangle)
Certifications		
Certifications		CE (EN55032, EN55024, EN50130-4) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)
Port		
Video Output		Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Audio Input		One channel built-in mic
Power		
Power Supply		12 V ±30% DC
Power Consumption		Max 2.38 W (12 V DC, IR on)
Environment		
Operating Temperature		−40 °C to +60 °C (−40 °F to 140 °F);< 95% (non-condensation)
Storage Temperature		−40 °C to +60 °C (−40 °F to 140 °F);< 95% (non-condensation)
Protection Grade		IP67
Structure		
Casing		Metal throughout the whole casing
Camera Dimensions		Φ62.0 mm × 61.7 mm (Φ2.44" × 2.43")
Net Weight		0.17Kg (0.40 lb)
Gross Weight		0.22Kg (0.50 lb)

Ordering Information		
Type	Model	Description
2M Camera	DH-HAC-HDW1231GP-A	2MP Starlight HDCVI IR Eyeball Camera, PAL
	DH-HAC-HDW1231GN-A	2MP Starlight HDCVI IR Eyeball Camera, NTSC
Accessories (Optional)	PFM800-E	Passive HDCVI Balun
	PFM321	12V 1A Power Adapter
	PFM904	Integrated Mount Tester

Accessories

Optional:



PFM800-E
Passive HDCVI Balun



PFM321
12V 1A Power Adapter



PFM904
Integrated Mount Tester

Dimensions (mm[inch])

